


Solid HSS & Cobalt Boring Bars

- M-35 High Speed Cobalt Steel-PC60.
- The massive head behind the cutting edge promotes rigidity and long life by reducing vibration.
- Supplied in wooden stand.



3/8" Shank

Shank Dia.	Length	Bore Depth	Min. Bore	M35 Cobalt	M42 Cobalt
A	B	C	D	Order No.	Order No.
3/8	1-13/16	9/16	3/16	375-5008	375-4008
3/8	2-3/16	15/16	3/16	375-5012	375-4012
3/8	2	3/4	1/4	375-5016	375-4016
3/8	2-1/2	1-1/4	1/4	375-5020	375-4020
3/8	2-3/16	15/16	5/16	375-5024	375-4024
3/8	2-13/16	1-9/16	5/16	375-5028	375-4028
3/8	2-3/8	1-1/8	3/8	375-5032	375-4032
3/8	3-1/8	1-7/8	3/8	375-5036	375-4036
8 Piece Set of Above				375-1007	375-1009

3/4" Shank

Shank Dia.	Length	Bore Depth	Min. Bore	M35 Cobalt	M42 Cobalt
A	B	C	D	Order No.	Order No.
3/4	2-7/8	1-1/8	3/8	375-5120	375-4120
3/4	3-5/8	1-7/8	3/8	375-5124	375-4124
3/4	3-1/16	1-5/16	7/16	375-5128	375-4128
3/4	3-15/16	2-3/16	7/16	375-5132	375-4132
3/4	3-1/4	1-1/2	1/2	375-5136	375-4136
3/4	4-1/4	2-1/2	1/2	375-5140	375-4140
3/4	3-7/16	1-11/16	9/16	375-5144	375-4144
3/4	4-9/16	2-13/16	9/16	375-5148	375-4148
3/4	3-5/8	1-7/8	5/8	375-5152	375-4152
3/4	4-7/8	3-1/8	5/8	375-5156	375-4156
3/4	3-13/16	2-1/16	11/16	375-5160	375-4160
3/4	5-3/16	3-7/16	11/16	375-5164	375-4164
3/4	4	2-1/4	3/4	375-5168	375-4168
3/4	5-1/2	3-3/4	3/4	375-5172	375-4172
14 Piece Set of Above				375-1607	375-1609

1/2" Shank

Shank Dia.	Length	Bore Depth	Min. Bore	M35 Cobalt	M42 Cobalt
A	B	C	D	Order No.	Order No.
1/2	2-1/8	3/4	1/4	375-5040	375-4040
1/2	2-5/8	1-1/4	1/4	375-5044	375-4044
1/2	2-5/16	15/16	5/16	375-5048	375-4048
1/2	2-15/16	1-9/16	5/16	375-5052	375-4052
1/2	2-1/2	1-1/8	3/8	375-5056	375-4056
1/2	3-1/4	1-7/8	3/8	375-5060	375-4060
1/2	2-11/16	1-5/16	7/16	375-5064	375-4064
1/2	3-9/16	2-3/16	7/16	375-5068	375-4068
1/2	2-7/8	1-1/2	1/2	375-5072	375-4072
1/2	3-7/8	2-1/2	1/2	375-5076	375-4076
10 Piece Set of Above				375-1207	375-1209

5/8" Shank

Shank Dia.	Length	Bore Depth	Min. Bore	M35 Cobalt	M42 Cobalt
A	B	C	D	Order No.	Order No.
5/8	2-5/8	1-1/8	3/8	375-5080	375-4080
5/8	3-3/8	1-7/8	3/8	375-5084	375-4084
5/8	2-13/16	1-5/16	7/16	375-5088	375-4088
5/8	3-11/16	2-3/16	7/16	375-5092	375-4092
5/8	3	1-1/2	1/2	375-5096	375-4096
5/8	4	2-1/2	1/2	375-5100	375-4100
5/8	3-3/16	1-11/16	9/16	375-5104	375-4104
5/8	4-5/16	2-13/16	9/16	375-5108	375-4108
5/8	3-3/8	1-7/8	5/8	375-5112	375-4112
5/8	4-5/8	3-1/8	5/8	375-5116	375-4116
10 Piece Set of Above				375-1407	375-1409

Round Shank Indexable Insert Boring Bars

Individual

Shank Dia.	Length	Bore Depth	Min Bore	Insert Style	Order No.	TiN Coated Order No.
1/2	2-3/4	1-1/4	7/16	TCMT21.51	375-6001	375-6101
1/2	3-5/8	2-1/8	7/16	TCMT21.51	375-6002	375-6102
1/2	3	1-1/2	1/2	TCMT21.51	375-6003	375-6103
1/2	4	2-1/2	1/2	TCMT21.51	375-6004	375-6104
5/8	3	1-1/4	7/16	TCMT21.51	375-6005	375-6105
5/8	3-7/8	2-1/8	7/16	TCMT21.51	375-6006	375-6106
5/8	3-1/4	1-1/2	1/2	TCMT21.51	375-6007	375-6107
5/8	4-1/4	2-1/2	1/2	TCMT21.51	375-6008	375-6108
5/8	3-1/2	1-3/4	9/16	TCMT221	375-6009	375-6109
5/8	4-5/8	2-7/8	9/16	TCMT221	375-6010	375-6110
3/4	3-3/8	1-3/8	7/16	TCMT21.51	375-6011	375-6111
3/4	4-1/4	2-1/4	7/16	TCMT21.51	375-6012	375-6112
3/4	3-5/8	1-5/8	1/2	TCMT21.51	375-6013	375-6113
3/4	4-5/8	2-5/8	1/2	TCMT21.51	375-6014	375-6114
3/4	3-7/8	1-7/8	9/16	TCMT221	375-6015	375-6115
3/4	5	3	9/16	TCMT221	375-6016	375-6116
3/4	4-1/4	2-1/4	11/16	TCMT221	375-6017	375-6117
3/4	5-1/2	3-1/2	11/16	TCMT221	375-6018	375-6118

- Screw Down Style
- Poaitive rake 90 degree lead



Sets

Set Includes:

- Inserts
- Tors Screw
- Boring bars

No. of Pieces	Shank Size	Order No.	TiN Coated Order No.
4 Pcs/set	1/2"	375-6021	375-6121
6 Pcs/set	5/8	375-6022	375-6122
8 Pcs/set	3/4	375-6023	375-6123