

## Electronic Digital Indicators

### 5 Keys, Fraction

- Criterion A for ESD
- Metric-inch-fraction conversion;
- Data output
- Creadible power on reset
- Auto power-off(option)
- 3v Lithium battery CR2032.

| Range         | Graduation             | Order No. |
|---------------|------------------------|-----------|
| 0-12.7mm/0.5" | 0.01mm/0.0005"/ 1/128" | 605-2101  |
| 0-25.4mm/1"   | 0.01mm/0.0005"/ 1/128" | 605-2102  |

### 5 Keys, Large Screen

- Zero setting at any position
- Metric/Inch system conversion at any position
- TOL setting switch
- Maximum and minimum tracking switch
- With data output interface
- Outo shutdown

| Range        | Graduation      | Order No. |
|--------------|-----------------|-----------|
| 0-.5"/12.7mm | 0.001mm/0.0005" | 605-2071  |
| 0-1"/25.4mm  | 0.001mm/0.0005" | 605-2072  |
| 0-2"/50.8mm  | 0.001mm/0.0005" | 605-2073  |

### 5 Keys, Large Screen

- Maximum measurement speed:1.5m/s (0.001mm/0.0005")
- ON/OFF, ZERO, in/mm, ABS/INC, TOL
- Operating temperature: 0-40°C
- Power: 1.5V SR44(silver xide cell) 1 battery
- With data output interface

| Yellow Screen |               |           |           |
|---------------|---------------|-----------|-----------|
| Range         | Graduation    | Order No. | Order No. |
| 0-.5"/12.7mm  | 0.01mm/0.005" | 605-2631  | 605-2691  |
| 0-1"/25.4mm   | 0.01mm/0.005" | 605-2632  | 605-2692  |
| 0-2"/50.8mm   | 0.01mm/0.005" | 605-2633  | 605-2693  |

### 7 Keys Multi-Function Large LCD Screen

- Large LCD Screen.
- Featured extra function of Measuring Range and Measuring Direction setting.

| Range        | Graduation       | Shell Size | Stem Dia. | Order No. |
|--------------|------------------|------------|-----------|-----------|
| 0-13mm/1/2"  | 0.01mm/0.0005"   | 2-1/2"     | 9.5mm     | 605-2000  |
| 0-13mm/1/2"  | 0.01mm/0.0005"   | 60mm       | 8mm       | 605-2001  |
| 0-6.5mm/1/4" | 0.001mm/0.00005" | 2-1/2"     | 9.5mm     | 605-2020  |
| 0-6.5mm/1/4" | 0.001mm/0.00005" | 60mm       | 8mm       | 605-2021  |
| 0-13mm/1/2"  | 0.001mm/0.00005" | 2-1/2"     | 9.5mm     | 605-2035  |
| 0-13mm/1/2"  | 0.001mm/0.00005" | 60mm       | 8mm       | 605-2036  |

| Range     | Graduation      | Shell Size | Stem Dia. | Order No. |
|-----------|-----------------|------------|-----------|-----------|
| 0-25mm/1" | 0.01mm/0.0005"  | 2-1/2"     | 9.5mm     | 605-2002  |
| 0-25mm/1" | 0.01mm/0.0005"  | 60mm       | 8mm       | 605-2003  |
| 0-25mm/1" | 0.005mm/0.0001" | 2-1/2"x4"  | 9.5mm     | 605-2033  |
| 0-25mm/1" | 0.005mm/0.0001" | 64x100mm   | 8mm       | 605-2034  |

## Dial Depth Gages

- Provides rapid, direct reading measurements of hole depths.
- 0-1" Travel indicator with 0.001" Graduation.
- Supplied with fitted case.

| Range | Base Size | No. of Rods | Order No. |
|-------|-----------|-------------|-----------|
| 0-4"  | 2-1/2"    | 4           | 615-6130  |
| 0-4"  | 4"        | 4           | 615-6131  |
| 0-6"  | 2-1/2"    | 6           | 615-6132  |
| 0-6"  | 4"        | 6           | 615-6133  |
| 0-8"  | 2-1/2"    | 8           | 615-6134  |
| 0-8"  | 4"        | 8           | 615-6135  |
| 0-12" | 2-1/2"    | 12          | 615-6136  |
| 0-12" | 4"        | 12          | 615-6137  |

- Provides rapid, direct reading measurements of hole depth
- 2 extra points: one 0.078" dia x 1" long, one needle point x 1" long (Order No. 605-0068)
- Furnished in fitted case

| Range | Rod Size | Base Size | Grad.  | No. of Rods | Order No. |
|-------|----------|-----------|--------|-------------|-----------|
| 0-8"  | 1,2,4"   | 2-1/2"    | 0.001" | 3           | 615-6144  |
| 0-8"  | 1,2,4"   | 4"        | 0.001" | 3           | 615-6145  |
| 0-22" | 1-6"     | 2-1/2"    | 0.001" | 6           | 615-6139  |
| 0-22" | 1-6"     | 4"        | 0.001" | 6           | 615-6138  |

## Electronic Digital Indicator Depth Gages

### 3 keys, large LCD Screen

- Provides rapid, direct reading measurements of hole depth
- Furnished in fitted case

- Provides rapid, direct reading measurements of hole depth
- Furnished in fitted case

| Range       | Graduation     | Base Size | No. of Rods | Rod Size | Order No. |
|-------------|----------------|-----------|-------------|----------|-----------|
| 0-200mm/8"  | 0.01mm/0.0005" | 2-1/2"    | 3           | 1,2,4"   | 605-6813  |
| 0-200mm/8"  | 0.01mm/0.0005" | 4"        | 3           | 1,2,4"   | 605-6814  |
| 0-550mm/22" | 0.01mm/0.0005" | 2-1/2"    | 6           | 1-6"     | 605-6815  |
| 0-550mm/22" | 0.01mm/0.0005" | 4"        | 6           | 1-6"     | 605-6816  |

- 2 extra points: one 0.078" dia x 1" long, one needle point x 1" long (Order No. 605-0068)

| Range       | Graduation       | Base Size | No. of Rods | Rod Size | Order No. |
|-------------|------------------|-----------|-------------|----------|-----------|
| 0-550mm/22" | 0.001mm/0.00005" | 2-1/2"    | 6           | 1-6"     | 605-6809  |
| 0-550mm/22" | 0.001mm/0.00005" | 4"        | 6           | 1-6"     | 605-6810  |