

8 In 1 Digital Tyre Gage

Features:

- Multi-scales: PSI, Bar, Kg/cm², Kpa
- Digital tread depth gauge(mm/inch)
- Bright LED flash light
- Back lighted LCD for use in the dark
- Bleeder valve for pressure adjustment
- The hammer easily shatters glass to free when doors are jammed on land or under water
- The seatbelt cutter quickly slices through a jammed
- With Compass
- Operation Temp.: -5°C~+50°C
- Power: 3 PCS AAA batteries
- Measuring Range: 0-200PSI



Order No. 856-0312

Mini Digital Tyre Gage

- Large LCD display for easy reading
- Mini size and lightweight
- Can be attached to key ring, and it is a good choice for promotion
- Single key operation, manual or auto power on/off, unit conversion,
- Four units in measuring pressure: PSI, Bar, Kg/cm², Kpa
- Range: 0-100PSI, 0-7.0Bar, 0-7.0Kg/cm², 0-700Kpa or 0-200PSI, 0-14Bar, 0-14Kg/cm², 0-140Kpa
- Can order named color
- Resolution: 0.1PSI, 0.01Bar, 0.01Kg/cm², 1Kpa
- Accuracy: +/-1%
- Working temp: -5-50 Degree
- Dimensions: 61.5x40x13mm



Order No. 856-0309

Ultrasonic Dimension Pro with Laser

Accurate within 0.5%+1 digit Measure interior room dimensions up to 41 feet (12.0meters). Fast and easy estimates for carpet, tile and wallpaper easy to read LCD display outperform 00ms traditional tape measures, FT/Meter conversion function.

- Measurement Range: 55cm to 12.0m (against hard surface)
- Accuracy: +/- (0.5%+1 digit)(in still air)
- Resolution: 0.01m
- Aperture Angle: Approximately 7°
- Calculation Range: Length: ~ 150.00m Area: ~ 144.00m² Volume: ~ 1500.00m³



Order No. 856-0244

Mfr's #: EM55

Digital Torque Wrenches

Features:

- Longer battery life due to low energy consumption.
- The application point of the force is not restricted
- Tile functions are monment measuring, max, moment tracking(holding the max. value), setting moment limit value and data output functions.
- Alternative construction of the moment type or the couple type.
- Accuracy: +/-2%.

Couple Type



Range (N.m)	Resolution (N.m)	OAL (mm)	Square Tenon (mm)	Order No.
8-15	0.1	360	12.5x12.5	856-0281
10-20	0.1	360	12.5x12.5	856-0282
15-50	0.1	460	12.5x12.5	856-0283
20-60	0.1	460	12.5x12.5	856-0284
40-100	0.1	460	12.5x12.5	856-0285
45-120	0.1	460	12.5x12.5	856-0286
50-150	1	540	12.5x12.5	856-0287
60-200	1	540	12.5x12.5	856-0288

Moment Type



Range (N.m)	Resolution (N.m)	OAL (mm)	Square Tenon (mm)	Order No.
0.3-1.5	0.001	252	6.3x6.3	856-0261
0.6-3	0.001	252	6.3x6.3	856-0262
3-10	0.01	252	6.3x6.3	856-0263
5-15	0.01	252	6.3x6.3	856-0264
8-20	0.1	275	10x10	856-0265
10-25	0.1	275	10x10	856-0266
15-50	0.1	370	12.5x12.5	856-0267
20-60	0.1	370	12.5x12.5	856-0268
20-100	0.1	410	12.5x12.5	856-0269
30-150	0.1	460	12.5x12.5	856-0270
40-200	0.1	460	12.5x12.5	856-0271
50-250	0.1	490	12.5x12.5	856-0272
60-300	0.1	490	12.5x12.5	856-0273
100-350	1	490	20x20	856-0274
120-400	1	490	20x20	856-0275
150-500	1	590	20x20	856-0276
180-600	1	590	20x20	856-0277
220-800	1	1119	20x20	856-0278
300-1000	1	1119	20x20	856-0279