

Edge & Center Finders

- Helps ensure accuracy by releasing an audible click when the tip jumps.
- Available in three sizes: 1/2", 3/8" and 10mm.
- Hardened and ground on all working surface.

Center Finders



Shank Dia.	Order No.
3/8"	805-3131
1/2"	805-3133

Combo Edge/Center Finders



Shank Dia.	Tip Dia.	Order No.
3/8"	.200"	805-3141
1/2"	.200"	805-3143

Micro Edge Finders



Shank Dia.	Tip Dia.	Order No.
3/8"	.200"	805-3121
3/8"	10mm	805-3127
1/2"	.200"	805-3123
1/2"	.500"	805-3125
10mm	10mm	805-3129

Edge Finders



Shank Dia.	Tip Dia.	Order No.
3/8"	10mm	805-3161
1/2"	.500"	805-3165
10mm	10mm	805-3163

Rotary Edge Finders



Shank Dia.	Tip Dia.		Order No.
3/8"	4mm	Large Shoulder Joint	805-3111
3/8"	6mm		805-3115
3/8"	10mm	Large Shoulder Joint	805-3113
10 mm	4mm	Large Shoulder Joint	805-3101
10 mm	6mm	Large Shoulder Joint	805-3105
10 mm	10mm		805-3103

Shank Dia.	Tip Dia.		Order No.
3/8"	.20"	single end	805-3112
1/2"	.20"	single end	805-3116
1/2"	.20"/.50"	Double end	805-3118



Electronic Edge Finders

- Repeatability within .0002"/0.005mm.
- Made of stainless steel.
- Feature LED light.
- Two 1.5V cell batteries included.
- With 10mm diameter probe.



Beep Alert

Repeatability	Shank Dia	Overall Length	Order No.
.0002"/0.005mm	3/4"/20mm	7-1/2"/190mm	805-3017
.0002"/0.005mm	1-1/4"/32mm	7-1/2"/190mm	805-3018



Short Shank

Repeatability	Shank Dia	Overall Length	Order No.
.0002"/0.005mm	3/4"/20mm	3-7/8"/97mm	805-3011
.0002"/0.005mm	1-1/4"/32mm	3-7/8"/97mm	805-3012

Long Shank

Repeatability	Shank Dia	Overall Length	Order No.
.0002"/0.005mm	3/4"/20mm	6-7/10"/170mm	805-3015
.0002"/0.005mm	1-1/4"/32mm	6-7/10"/170mm	805-3016

Center Finder Set

For accurately locating working points on drill presses, milling and other machines

Individual

Description	Order No.
.236" Indicator Holder	805-3311
.250" Ball Contact	805-3312
Chuck Body	805-3313
.100" Disc Contact	805-3314
Needle Point	805-3315




Set Order No. 805-3305

Magnetic Stands

- Accepts all A.G.D dial indicators with lug backs.
- Accepts dial test indicator stems .375"/9.52mm dia. and .156"/3.96mm dia.
- On and off lever releases magnet, base doesn't have to be pulled off, no risk of marring polished surfaces.
- Universal adjustment in horizontal and vertical planes.
- Quick adjustment clamp.

Base Only with Switch On/Off

Magnetic Power	Dimensions	Order No.
40kgs	63x50x55mm M8	625-0940
60kgs	63x50x55mm M8	625-0960
70kgs	70x45x65mm M10	625-0961
80kgs	70x50x55mm M8	625-0980
80kgs	70x50x55mm M10	625-0981
100kgs	88x50x55mm M10	625-0982



Standard

Fine Adjustment

Magnetic Power	Working Stem	Base Size	Standard Order No.	With Fine Adjustment Order No.
40kgs	176mm/12mm	63x50x55mm	625-0300	625-0340
60kgs	176mm/12mm	63x50x55mm	625-0301	625-0341
80kgs	176mm/12mm	70x50x55mm	625-0302	625-0342
60kgs	225mm/16mm	63x50x55mm	625-3301	625-3341
80kgs	225mm/16mm	70x50x55mm	625-3302	625-3342
100kgs	360mm/20mm	88x50x55mm		625-0360

Universal Magnetic Base Holders

- Multi-nimble joint for instant fixation in any position.
- Fits dovetail & 3/8" or 8 mm stem indicator.
- Fine adjustment knob.
- On-off switch on base.



Steel Arm Alloy Arm

Magnetic Power	Base Size	Steel Arm Order No.	Alloy Arm Order No.
40kgs	2x2x2-1/8"	625-1140	625-1141
60kgs	2-1/2x2x2-1/8"	625-1160	625-1161
80kgs	2-3/4x2x2-1/8"	625-1180	625-1181

Hydraulic Universal Magnetic Stands

- Unique hydraulic clamping system.
- Can hold all style dial indicators and dial test indicators.
- On-off switch base.



Magnetic Power	Working Stem	Base Dimension	Steel Arm Order No.	Alloy Arm Order No.
40kgs	380	63x50x55mm	625-1340	625-1342
60kgs	380mm	63x50x55mm	625-1360	625-1362
80kgs	380mm	70x50x55mm	625-1380	625-1382

Flexible Stem Magnetic Base Holders

- Stem flexes almost 360 degree.
- Locks into exact position with a cam lever-operated cable and tension adjustment.
- Accept all AGD type indicator

Power	Base Size	Order No.
40kgs	2-1/2x2x2-1/8"	625-1040
60kgs	2-3/4x2x2-1/8"	625-1060
80kgs	2-3/4x2x2-1/8"	625-1080



Flexible Stem Magnetic Base Holders

- Accept dial test indicators, digital indicators and normal indicators
- Locks into exact position with a cam lever-operated cable and tension adjustment.
- Dovetail groove for clamping a dial test indicator, end hole with bushing for holding 3/8" stem or 8mm stem.
- Stem Length 360mm

Power	Base Size	Order No.
40kgs	2-1/2x2x2-1/8"	625-1081
60kgs	2-3/4x2x2-1/8"	625-1082
80kgs	2-3/4x2x2-1/8"	625-1083



Flexible Indicator Holder

- Ideal for very tight work areas.
- Mounted pot magnetic base - 1-3/8" diameter x 1-1/8" high, 25 lbs. pull with 5" post and fine adjustment.

Order No. 625-0575



- Ideal for very tight work areas
- Mounted pot magnetic base- square, 25 lbs. pull with 5" post and fine adjustment
- Indicator not included

Order No. 625-1025



Flexible Arm Magnetic Base Holder

This product is made under the advanced technology .It is an ideal tool used for trusting random angle and internal hole.

Magnetic Power: 60kgs
Stem Length: 360mm
Stem Diameter: 16mm
Base Size: 60x50x55mm

OrderNo.625-0950



Easy Lock Universal Magnetic Bases

- Multi-nimble joint for instant fixation in any position.
- Fits dovetail & 3/8" or 8 mm stem indicator.
- Fine adjustment knob.
- On-off switch on base.
- Indicator not included

Power	Base Size	Order No.
40kgs	2-1/2x2x2-1/8"	625-1084
60kgs	2-3/4x2x2-1/8"	625-1085
80kgs	2-3/4x2x2-1/8"	625-1086



Extra Stem Magnetic Bases

- Fine adjustment.
- On-off switch on base.
- Extra Stem, one main stem, two branch stems

Power	Base Size	Main Stem	Order No.
60kgs	60x50x55mm	φ20x170mm	625-0350
80kgs	73x50x55mm	φ20x400mm	625-0351



DIN Magnetic Stands

- 70 kg pull, switch On/Off base 70x45x65mm. M10
- Working stem φ16x230mm/φ12x200mm. M10
- With fine adjustment.

Description	Order No.
Base & Holder Set	625-0343
Dial Gage Holder Only	625-0201
Base Only	625-0961



Plastic Casing Magnetic Stand

Magnetic Power: 60lbs/30kgs
Overall Height: 6"
Branch Column Length: 4-1/2"
Base Size: 1-1/2x1-1/2x1-3/4"
Weight: 2.1lbs

Order No. 625-0015



SL Series Magnetic Stand

with fine guide screw adjustment

- Feature fine guide screw adjustment
- With different magnetic base
- Accept dial test indicator
- Stems: $\phi 8.0$ or $\phi 3/8$ "
- Main stem: $\phi 12 \times 190$ mm
- Height gage bar
- Branch stem: $\phi 10 \times 190$ mm



Order No. 625-0017

Vacuum Base Holder

With Suction Base


- Standard holder mounted on a powerful Vacuum Base
- Most useful on granite plates or other non-magnetic smooth surface
- features an 80mm diameter powerful suction pad
- ON/OFF lever for easy attaching of removing
- 3-1/2" Dia, M8x1.25 Mounting



Order No. 625-0041



Order No. 625-0042



Order No. 625-0040

Surface Gages

- Base and scriber are hardened.
- Bottom grooved for cylindrical work.
- Front recessed for depressing spindle below base level.
- Features fine adjustment.
- Base has 2 retractable gage pins to set against edge of a surface plate.
- Test indicator order No. 605-4710.



Surface gages

Description	Order No.
4 & 7" Spindles	625-8550
9 & 12" Spindles	625-8560
12 & 18" Spindles	625-8570

Surface gage and Test Indicator Sets

Description	Order No.
4&7" Spindles & Test indicator 0.03x.0005"	625-8555
9&12" Spindles & Test indicator 0.03x.0005"	625-8565
12&18" Spindles & Test indicator 0.03x.0005"	625-8575

Hydraulic Universal Magnetic Stands

Base with hydraulic clamping system



Magnetic Power	Working Stem	Base Dimension	Order No.
30kgs	320mm	Dia.40x H30mm	625-1320

Anyform Magnetic Base Indicator holder

- Attaches firmly to any shape or contour
- Dovetail attachment(include)-the unit accommdates AGD and test indicator
- Cam-lock mechanism for fine adjustment
- Powerful permanent magnet.



Range	Order No.
Base Only	625-0481
Base with standard arm and clamps	625-0482
Base with fine adjustment arm and clamps	625-0483
Base with Flexible arm	625-0484
Base with hydraulic clamping system	625-0485

Universal Measuring Stands

Main Column Length: 150mm
Branch Column Length: 225mm
Base Size: 225x58x35mm
Weight: 3.2kg

Description	Order No.
with Fine Adjustment	625-0012
Without Fine Adjustment	625-0010



Magnetic Base Indicator Holder & Sets

- Six mounting locations for indicators and accessories.
- Three 1/4"-20 tapped holes, one 10-32 tapped hole, one 3/8" mounting hole, one V-shaped Mounting Hole.
- Size: 4"x1"x1".



Versatile , Powerful, Compact & Rugged

Descriptions	Order No.
Tiny-Titan Base	625-0450
Base & 1" dial indicator (605-4070)	625-0455
Base & 2" dial indicator (605-4205)	625-0460

Economy Magnetic Bases

- Single Universal Rod, has 3 diameters to permit mounting popular indicators without changing rods.
- Non magnetic ball seat is riveted directly to the pole piece for permanent anchorage and lifetime rigidity.
- Non-breakable plastic base.
- Strong Magnetic Pull.
- Full 360° swivel.



Style A

Style B

Description	Order No.
Style A	625-0920
Style B	625-0922

Fine Quality Magnetic Base Holder

A permanent alnico magnetic base that easily attaches to any steel or iron surface in any desirable or convenient position, eliminating the use of clamps. The adjustable post assembly swivels into a 40° desired position and has a fine adjusting screw for final setting. Although intended primarily for test indicators, it is just as handy for inspection magnifiers, mirrors, safety shields, oil sprays, air lines, etc. Base diameter 1-1/4", with approximate 5-1/4" fine pivot adjustment post.



	Order No.
magnetic Base	625-0400

Mini Magnetic Bases

- Articulated arm style magnetic base positions and lock easily.
- Size of Magnetic Base: 30x30x30mm/1-1/5x1-1/5x1-1/5".
- One knob mechanically tightens both arms.
- Overall Stem Length: 12".



Switch On/Off
Order No. 625-2627



Push Button On/Off
Order No. 625-2617

Universal Magnetic Indicator Holders

- Excellent workmanship on many applications.
- Fine adjustment clamp.
- Dovetail clamp for test indicator.
- 1/4" holes for 1/4" stem indicator.
- All knurled knobs and lock screws.



Square Base

Circular Pot Base

Circular Pot Base

Description	Order No.
Circular Pot Base	625-0515
Circular Pot Base	625-0520
Square Base	625-0510

Push Button Magnetic Bases


Type A

- Provided with ON/OFF push button.
- Especially designed for use with dial gages, to work on surface plate and machine table.
- Complete with 18kgf powerful magnet.

Order No. 625-0900

Type B

- Provided with ON/OFF push button.
- Especially designed for use with dial gages, to work on surface plate and machine table.
- Complete with 50kgf powerful magnet.



Description	Order No.
with Fine Adjustment	625-0910
Without Fine Adjustment	625-0905

Mini Magnetic Stands

Standard Model

- Height of base: 1"
- Diameter of base: 1"

Description	Order No.
with Fine Adjustment	625-0562
Without Fine Adjustment	625-0560

With Rod

- Height of base: 1"
- Diameter of base: 1"
- Height of rod: 3-1/2"
- Diameter of rod: 1/4"

Description	Order No.
with Fine Adjustment	625-0572
Without Fine Adjustment	625-0570



Magnetic Base Indicator Holders

Full magnetic base. Non-magnetic stainless steel holding rod, set in hardened universal ball socket. Fine precision adjustment controlled by thumb screw allowing minute adjustments. Hammered blue base finsh...other parts are chrome plated or stainless steel. Magnetic release.




without Arm with Centre Arm with Side Arm

Descriptions	High Rod	Order No.
3-1/2x1-1/8x1" without Arm		625-0470
3-1/2x1-1/8x1" with Centre Arm		625-0472
3-1/2x1-1/8x1" with Side Arm	6"x1/4"	625-0480

Universal Indicator Holder

- Clamping dia. 1-7/8".
- Length from clamping bracket to indicator 4-1/2".
- Suitable for all popular indicators with 5/32" shank or dovetail.
- Mounts with single pressure screw directly on machine quill, by passing the working tool.
- Guaranteed accurate readings.
- For milling machines & jig bores.
- A quicker way of indicating.
- Does not disturb the working tool.



Order No. 625-8522

Adjustable Magnetic Connector

Two permanent magnets for joining of parts in drilling ,scraping, welding , etc. Adjustable to any angle & secured by wing nuts.



2 bars 2x1x1"
Order No. 625-0115

Pot Magnets

- For use as magnetic fasteners.
- Comes with plated keeper.

Diameter	Height	Hole	Order No.
21/32"	5/8"	5/16"-18	625-0382
7/8"	3/4"	5/16"-18	625-0384
1-1/16"	1"	5/16"-18	625-0386
1-3/8"	1-3/16"	5/16"-18	625-0388



"UNI-MAG" Direct Mount Magnetic Base

- Permanent magnet.
- Fits all A.G.D. indicators

Size	Order No.
φ2-1/4 x 9/16"	625-0451
φ1-3/4 x 5/16"	625-0452



Square Type Magnetic Block

- Used as a holder for precision work in measuring, marking and other similar operation.
- Measuring available on the upper, side faces, V faces for irregular shape parts.
- The V face max measuring range: dia 20mm Bar.



V Face Magnetic Power	Flat face Magnetic Power	Square Size	Steel & Copper Order No.	Steel & Aluminum Order No.
25kgs	30kgs	100	625-2031	625-2034
35kgs	100kgs	150	625-2032	625-2035
70kgs	250kgs	200	625-2033	625-2036

Magnetizer & Demagnetizer

- Used for Screw Driver/Small Parts

Size	Order No.
2x2x1"	625-0000



Portable Magnetizer/Demagnetizer

- Quickly magnetizes or demagnetizes drills,punches,dies, screwdrivers, simply by passing them through or near the loop.
- No physical contact needed.
- Portable and easy to used.
- Electrically & thermally protected.
- Operates on 110V AC 60 cycle with push button control.



Order No. 285-2700

Demagnetizers

- Demagnetize dies, punches, cutters, or any tools that have become magnetized.
- Operates on 115/220V AC with on /off switch.



Volt	Table Size	Order No.
110V	6-3/4" x 4-1/4"	285-2505
220V	170mm x 108mm	285-2605



Volt	Table Size	Order No.
110V	190x120mm	285-2805
110V	210x152mm	285-2808
220V	190x120mm	285-2815
220V	210x152mm	285-2818