

Dial Indicators

Inch Size



Range	Grad.	Dial Reading	Dial Size	Back Lug	Order No.
0.05"	.0001"	0-100	2.28"	With	605-4000
0.125	.0005	0-25-0	1-37/64	With	605-4002
0.125	.00025	0-100	1-37/64	With	605-4003
0.25	0.001	0-100	2.28	With	605-4030
0.25	0.001	0-100	2.28	With	605-4031*
0.25	0.001	0-50-0	2.28	With	605-4035
0.25	0.001	0-100	1-37/64	Without	605-4041
0.25	0.001	0-100	1-37/64	With	605-4040
0.25	0.0005	0-100	2.28	With	605-4005**
0.25	0.0005	0-100	1-37/64	With	605-4004
0.25	0.0005	0-50	2.28	With	605-4058
0.25	0.0001	0-100	2.28	With	605-4006
0.40	0.001	0-100	2.28	With	605-4045
0.5	0.001	0-100	2.28	With	605-4050
0.5	0.001	0-100	2.28	With	605-4051*
0.5	0.001	0-100	2.28	Without	605-4605
0.5	0.001	0-50-0	2.28	With	605-4055
0.5	0.0005	0-100	2.28	With	605-4052
0.5	0.0005	0-50	2.28	With	605-4060
0.5	0.0005	0-25-0	2.28	With	605-4065
0.5	0.0001	0-100	2.28	With	605-4012
1	0.001	0-100	2.28	With	605-4070
1	0.001	0-100	2.28	With	605-4080***
1	0.001	0-50-0	2.28	With	605-4075
1	0.0005	0-100	2.28	With	605-4071
1	0.0005	0-50	2.28	With	605-4063
1	0.0001	0-100	2.28	With	605-4025
2	0.001	0-100	2.28	With	605-4205
2	0.001	0-100	2.28	With	605-4206***

* Economy Dial Indicators.

** without Rev.Counter.

*** Black Face

Metric Size

Range (mm)	Grad. (mm)	Dia. (mm)	Back Lug	Style	Order No.
0.5	0.001	40	With		605-4305
0.8	0.001	40	With		605-4308
1	0.001	40	Without	6 Jeweled	605-4100
1	0.001	40	With	6 Jeweled	605-4301
1	0.001	58	Without	6 Jeweled	605-4101
3	0.01	40	With		605-4110
3	0.01	40	With	6 Jeweled	605-4311
3	0.01	40	Without		605-4120
3	0.01	40	Without	6 Jeweled	605-4310
3	0.01	58	With		605-4236
3	0.01	58	With	Shock Proof	605-4235
3	0.01	58	Without		605-4232
3	0.01	58	Without	Shock Proof	605-4230
3	0.001	50	Without		605-4103
5	0.01	58	With		605-4130
5	0.01	58	Without		605-4115
5	0.01	58	Without	6 Jeweled	605-4330
5	0.01	58	With	6 Jeweled	605-4331
5	0.01	40	Without		605-4140
5	0.001	58	Without	6 Jeweled	605-4345
8	0.01	40	With		605-4108
8	0.01	40	Without		605-4145
10	0.01	58	With		605-4151
10	0.01	58	Without		605-4125
10	0.01	58	Without	6 Jeweled	605-4136
10	0.01	58	With		605-4360
10	0.01	60	With	6 Jeweled	605-4350
10	0.01	60	Without	6 Jeweled	605-4351
15	0.01	58	With		605-4150
20	0.01	58	With		605-4190
25	0.01	58	Without	6 Jeweled	605-4160
30	0.01	58	With		605-4165
30	0.01	58	Without		605-4166
50	0.01	76	With		605-4170
50	0.01	76	Without		605-4180

Dual System Dial Indicators

Inch/Metric:

Inch Outside, Metric Inside

Inch/Metric Dial Indicators

Range	Dial Dia.	Graduation	Order No.
0-1/2"/0-15mm	2-3/8"	0.001"/0.1mm	605-4815
0-1"/0-25mm	2-3/8"	0.001"/0.1mm	605-4816

Inch/Metric Dial Indicators

Range	Dial Dia.	Graduation	Order No.
0-1"/0-25mm	3"	0.001"/0.1mm	605-4819
0-1.5"/0-40mm	3"	0.001"/0.1mm	605-4820
0-2"/0-50mm	3"	0.001"/0.1mm	605-4821

Metric/Inch:

Metric Outside, Inch Inside

Metric/Inch Dial Indicators

Range	Dial Dia.	Graduation	Order No.
0-15mm/0-.5"	2-3/8"	0.1mm/0.001"	605-4817
0-25mm/0-1"	2-3/8"	0.1mm/0.001"	605-4818

Metric/Inch Dial Indicators

Range	Dial Dia.	Graduation	Order No.
0-25mm/0-1"	3"	0.1mm/0.001"	605-4822
0-40mm/0-1.5"	3"	0.1mm/0.001"	605-4823
0-50mm/0-2"	3"	0.1mm/0.001"	605-4824

Crankshaft Meter

- Measuring rang: 45-500mm
- Rotatable dial.
- Delivery complete with extensions in case.

Range	Graduation	Order No.
45-500mm	0.01mm	605-3830

