

Gear Driven Ring Roller

Precision, high quality machined roller forms rings out of not rolled flat stock, Metal sizes 3/16"x1" and up to 1/4" round, Create rings from 3" diameter to as large as you need. All surface are heat-treated and hardened for long life.



Order No.130-1111

Power Roll

Product Description
Capacity.....50" x 16 gage.
Motor.....
..220V/440V, 3-PH., 1HP.
Roll speed.....22 RPM.
Dia. of roll.....3".
Min. radius.....1.5".




Order No.130-5116

Rotary Machine

- Performs burring, edging, elbowing, flanging, flattening and turning.
 - Long throat makes unit highly versatile.
 - Includes 6 rolls: 2 turning, 1 each of burring, wiring, crimping, and ogee bead.
 - Standard clamp for table mount operation.
- Cutting Capacity.....22Gage
Distance Between Shaft Centers.....
.....2" (50.8mm)
Depth of Throat to Frame.....7"(175mm)
Net Weight.....64Lbs(29 kgs)
Gross Weight.....71Lbs(32kgs)
Overall Dimension (LXWXH).....
.....16"x8"x16"(458x203x406mm)



Order No. 130-5400



Slip Rolls

- Maximum gauge capacities are applicable when using mild steel.
- Using galvanized steel lowers the maximum gauge capacity.



Order No. 130-3622

Order No. 130-5016

Capacity	Dia.of Rolls	Weight	Slip Rolls Order No.	Optional Stands Order No.
12"x22Ga.	1"	37lbs	130-1222	130-1229
24"x20Ga.	2"	140lbs	130-2420	130-2429
36"x22Ga.	2"	280lbs	130-3622	130-3629
50"x16Ga.	3"	570lbs	130-5016	130-5019

Power Table Feeds

135 or 150lbs /inch of torque for mills with 5/8 Lead Screw

- Fits most Bridgeport and Bridgeport type milling machines.
- Speed: 4-180 RPM.
- Bevel Drive Gear Rate 4:8:1, Pilot light.
- A pivot light, on/off switch.
- Protective circuit breaker.
- Travel stop/limit, Internal Clutch, Helical Gearing.
- Strengthened Nylon "spiral gear".
- Automatic shutoff with electric limit switches.
- Central knob to control speed.
- Push button turns motor on for rapid traverse.
- Single lever controls engage, disengage, start, stop and direction of feed.
- Safety limit switches.



Axis	Volt/Frequency	Torque	Order No.
X-axis	115V/60Hz	135lbs	199-1050
X-axis	115V/60Hz	150lbs	199-1051
X-axis	240V/50Hz	135lbs	199-1049
Y-axis	115V/60Hz	135lbs	199-1052
Y-axis	115V/60Hz	150lbs	199-1053
Y-axis	240V/50Hz	135lbs	199-1054
Z-axis	115V/60Hz	150lbs	199-1055
Z-axis	240V/50Hz	135lbs	199-1056
Feed Horizontal type	115V/60Hz	150lbs	199-1057
Feed Horizontal type	240V/50Hz	135lbs	199-1058

Parts Washers

This parts washer is design for use in shops ranging from the home mechanic garage to heavy industry. Feature: enclosed pump, seamless construction.



Order No. 199-1035



Order No. 199-1043



Order No. 199-1026



Order No. 199-1022

Capacity	Order No.
3.5 gallon (portable style)	199-1035
6gallon	199-1026
20 gallon	199-1022
30 gallon	199-1030
40 gallon	199-1040
50 gallon	199-1043